



Product Specifications

P034078-016-436

DFT ULTRA-WEB CONDUCTIVE FR
CARTRIDGE FILTER 352 MM OD X 660
MM L (13.84" OD X 26.00" L)

Ultra-Web Conductive Flame Retardant Cartridge Filter, 352 mm outer diameter X 660 mm long (13.84-inch outer diameter X 26.00-inch long), Open/Open Endcaps for AerTable (Round Access Cover), CX, Downdraft Bench 2000 and 3000, Downflo II and other brands of cartridge collectors. 51 mm (2-inch) Pleat Height

Attributes

Outer Diameter	13.84 inch (352 mm)
Length	26.00 inch (660 mm)
Media Type	Ultra-Web Anti-Static
Filter Area	254 ft ² (23.60 m ²)
Inner Diameter	9.48 inch (241 mm)
Temperature Limit	180 °F (82 °C)
Liner	Yes
End Cap Construction	Open/Open
Construction	Galvanized
Shape	Round

Pleat Height	2.00 inch (51 mm)
Anti-Static	Yes
Flame Retardant	Yes
Current Brand	Donaldson Torit

Packaged Dimensions

Packaged Length	16.2 IN
Packaged Width	16.1 IN
Packaged Height	28.5IN
Packaged Weight	14.16 LB
Packaged Volume	4.3017 FT3

Other Information

Country of Origin	United States
NMFC Code	069100-06
HTS Code	8421390115

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that accompanies the goods.