

Features

- Low initial pressure drop
- Electrostatic Charged Media
- Dual Stage Filtration to enhance depth loading
- Superior Dust Holding Capacity
- Available in standard and custom sizes
- Available with antimicrobial

Ideal for:

- Hospitals
- Schools
- Office Complexes
- Food and Pharmaceutical processing
- Data Centers
- Computer Rooms
- Airports
- Paint Booths



Performance Data

Rating	MERV 13 @ 1968CFM
Dust Holding Capacity	110 grams
Initial Resistance	.31 in w.g
Final Resistance	1.50 in w.g.
Maximun operating temperature 180 degrees F	

Construction

- Ultrasonically Sealed, stitched Pockets
- Double lock stitched pockets
- Aerodynamic internal channels
- UL 900 classified

Part Number Guide

Prefix	Efficiency	Filter Size W x H x D	Pockets	Gasket	Hanger	Header
AS = AS Series	MERV 13 94%		3P	Blank - None	Blank-none	<i>Example: AS1324242208F= AS Series Bag MERV 13 Efficient 24x24x22 8 pockets Gasket on air exit side of header</i>
			4P			
			5P	R = Rear Load	1-Loops, 2 corners	
			6P	F = Front Load	2-Middle of Pocket	
			7P	S=One Vertical Side		
			8P			
			9P	BS= Both Vertical Sides		
			10P			
			11P	P=Perimeter		
			12P			