



### Features

- Low initial pressure drop
- Electrostatic Charged Media
- Dual Stage Filtration to enhance depth loading
- Superior Dust Holding Capacity
- Available in standard and custom sizes
- Available with antimicrobial

### Ideal for:

- Hospitals
- Schools
- Office Complexes
- Food and Pharmaceutical processing
- Data Centers
- Computer Rooms
- Airports
- Paint Booths

### Performance Data

Rating	MERV 14 @ 1968CFM
Dust Holding Capacity	240 grams
Initial Resistance	.45 in w.g.
Final Resistance	1.50 in w.g.
Maximum operating temperature 200 degrees F	

### Construction

- Ultrasonically sealed stitched Pockets
- Aerodynamic internal channels
- UL 900 classified

### Part Number Guide

Prefix	Efficiency	Filter Size W x H x D	Pockets	Gasket	Hanger	Header
AS = AS Series	MERV 14 95%		3P	Blank - None	Blank-none	Blank-Standard 7/8"
			4P	R = Rear Load	1-Loops, 2 corners	CB- 1-1/8"
			5P			
			6P	F = Front Load	2-Middle of Pocket	<i>Example: AS1424242208F= AS Series Bag MERV 14 Efficient 24x24x22 8 pockets Gasket on air exit side of header</i>
			7P	S=One Vertical Side		
			8P	BS= Both Vertical Sides		
			9P			
			10P	P=Perimeter		
			11P			
			12P			