

Eaton DU2005-0001

Catalog Number: DU2005-0001

Eaton DU Duplex Low Pressure Filter, DU2005.25VG.10.E.P.-.FS.C.P.-.-AE.50.5,0.P.-.B, 25 VG, Glass fiber fleece (VG), Nitrile, 464 psi (32 Bar), Non-bypass



General specifications

Product Name	Catalog Number
Eaton DU Duplex Low Pressure Filter	DU2005-0001
Model Code	Product Length/Depth
DU2005.25VG.10.E.P.-.FS.C.P.-.-AE.50.5,0.P.-.B	790.1 mm
	Product Height
	796.02 mm
Product Width	Product Weight
337.8 mm	341.96 kg

Compliances

AD 2000
ATEX Directive 2014/34/EU
PED 2014/68/EU for mineral oil (fluid group 2), Article 4, Para. 3.

Product specifications

Connection type

5" SAE/ANSI flange

Filter type

Duplex filter

Material

EN-GJS-400-18-LT

Application

For continuous operation. Mount in suction, pressure or return lines

Specification

Standard

Code stamp

None

Filter fineness

25 VG

Filter media type

Glass fiber fleece (VG)

Fluid group (DGRL 2014/68/EU)

2

Indicator type

Electrical/Visual

Sealing material

Nitrile

Element collapse rating

145 psi (10 Bar)

Operating temperature - max

100 °C

Operating temperature - min

-10 °C

Valve configuration options

Non-bypass

Operating pressure - max

464 psi (32 Bar)

Resources

Brochures

[Refrigeration overview US](#)

[Hydraulic and Lubrication Oil Filters US](#)

Technical data sheets

[DU 2005 4005 2153H US](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)