

# Eaton DWF6005-0000

Catalog Number: DWF6005-0000

Eaton DWF Duplex Low Pressure Filter , DWF.6005.10VG.10.E.P.-.FS.E.-.IS21.-, 10VG, Glass fiber fleece (VG), Nitrile, 232 psi (16 Bar), Non-bypass



## General specifications

Product Name	Catalog Number
Eaton DWF Duplex Low Pressure Filter	DWF6005-0000
Model Code	Product Length/Depth
DWF.6005.10VG.10.E.P.-.FS.E.-.IS21.-	1535.94 mm
Product Height	Product Width
1343 mm	540.01 mm
Product Weight	Compliances
749.79 kg	PED 2014/68/EU for mineral oil (fluid group 2), Article 4, Para. 3. ATEX Directive 2014/34/EU

## Product specifications

### Connection type

8" SAE/ANSI flange

### Filter type

Duplex filter

### Material

Carbon steel

EN-GJS-400-18-LT

### Application

For continuous operation. Mount in suction, pressure or return lines

### Specification

Standard

### Filter fineness

10 VG

### Filter media type

Glass fiber fleece (VG)

### Indicator type

None

### Sealing material

Nitrile

### Element collapse rating

145 psi (10 Bar)

### Operating temperature - max

100 °C

### Operating temperature - min

-10 °C

### Valve configuration options

Non-bypass

### Operating pressure - max

232 psi (16 Bar)

## Resources

### Brochures

[Condition Monitoring Systems US](#)

[Turbine Oil Application Brief US](#)

### Technical data sheets

[DWF-6005 TechnicalDataSheet 2230 US](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)