

Eaton DWF3005-0000

Catalog Number: DWF3005-0000

Eaton DWF Duplex Low Pressure Filter , DWF.3005.10VG.10.E.P.-.FS.C.-.IS21.-, 10VG, Glass fiber fleece (VG), Nitrile, 232 psi (16 Bar), Non-bypass



General specifications

Product Name	Catalog Number
Eaton DWF Duplex Low Pressure Filter	DWF3005-0000
Model Code	Product Length/Depth
DWF.3005.10VG.10.E.P.-.FS.C.-.IS21.-	1213.87 mm
Product Height	Product Width
1227.99 mm	445.01 mm
Product Weight	Compliances
295.75 kg	PED 2014/68/EU for mineral oil (fluid group 2), Article 4, Para. 3. ATEX Directive 2014/34/EU

Product specifications

Connection type

5" SAE/ANSI flange

Filter type

Duplex filter

Material

Carbon steel

EN-GJS-400-18-LT

Application

For continuous operation. Mount in suction, pressure or return lines

Specification

Standard

Filter fineness

10 VG

Filter media type

Glass fiber fleece (VG)

Indicator type

None

Sealing material

Nitrile

Element collapse rating

145 psi (10 Bar)

Operating temperature - max

100 °C

Operating temperature - min

-10 °C

Valve configuration options

Non-bypass

Operating pressure - max

232 psi (16 Bar)

Resources

Brochures

[Turbine Oil Application Brief US](#)

[Eaton-Fluid-Purifier-Systems-and-Oil-Service-Equipment-Brochure-US](#)

Technical data sheets

[DWF-3005 Technical Data Sheet 2228 US](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)