



PMC™ Series Filter Cartridges

*Economically Efficient
Pleated Filter Cartridges*

Product Specifications

Media: Polypropylene

Inner core, end caps, cage:
Polypropylene

Gaskets/O-Rings:

Buna-N, EPDM, Silicone, Teflon
Encapsulated Viton (O-Rings only),
Teflon (gaskets), Viton

Micron ratings:

0.2, 0.25, 0.45, 0.5, 1, 2, 5, 10, 25, 50 µm

Dimensions

Nominal lengths:

5", 9.75", 10", 19.5", 20", 29.25", 30",
39", 40"
(12.7, 24.8, 25.4, 49.5, 50.8, 74.3, 76.2,
99.1, 101.6 cm)

Outside diameter: 2.7" (6.86 cm)

Inside diameter: 1.0" (2.54 cm)

Operating Parameters

Maximum operating temperature:
176°F (80°C)

Maximum differential pressure:
75 psid @ 70°F (5.2 bar @ 21°C)
30 psid @ 176°F (2.0 bar @ 80°C)

Maximum reverse pressure:
40 psid @ 70°F (2.8 bar @ 21°C)

Recommended change-out pressure:
35 psid (2.4 bar)


This cost effective, disposable filter element can be used for a wide range of applications. The filter is constructed of pleated polypropylene filter media with high surface area that allows for greater system flow rate.

FEATURES & BENEFITS

- Micron ratings from 0.2 to 50 µm — Broad application range
- Fixed pore structures — Resists unloading of captured contaminant
- Polypropylene Construction — Inert to many process fluids
- Various Gasket/O-Ring materials — Compatible with a variety of fluids
- Economically efficient filtration
- Manufactured in continuous lengths up to 40 inches

CERTIFICATIONS

- USP Class VI: Meets USP Class VI Biological Test for Plastics
- FDA Listed Materials: All materials comply with FDA Title 21 of the Code of Federal Regulations Sections 174.5, and 177.1520, as applicable for food and beverage contact.
- European Directive for Direct Food Contact: European Regulation No. 1935/2004 and European Regulation 10/2011: Tested for migration behavior and is suitable for contact with all kinds of foodstuffs with minimal rinse-up. Data available upon request.




PMC NOMENCLATURE INFORMATION

Filter Type	Retention Rating (microns)		Nominal Length (inches)		End Configuration	Gasket or O-Ring		
PMC Series	0.2	2	-5	-29.25 ¹	P	Double Open End	B	Buna-N
	0.25	5	-9.75 ¹	-30	P2	226/Flat Single Open End	E	EPDM
	0.45	10	-10	-39 ¹	P3	222/Flat Single Open End	S	Silicone
	0.5	25	-19.5 ¹	-40	P7	226/Fin Single Open End	T	Teflon encap. Viton (O-Rings only) ²
	1	50	-20		P8	222/Fin Single Open End	T	Teflon Gasket
				P28	222 w/3 tabs/Fin Single Open End	V	Viton	
				AM	Single Open End, Internal O-Ring			
				NPC	Double Open End, Internal O-Ring			
Example: PMC 2-20P8V								
PMC	2		-20		P8		V	

¹Available only for DOE (P) configuration ²Not available in AM style

PMC FLOW RATE

Typical Flow Rate Clean Water at Ambient Temperature
(per 10" cartridge)



The micron ratings shown at various efficiency and beta ratio value levels were determined through laboratory testing, and can be used as a guide for selecting cartridges and estimating their performance. Under actual field conditions, results may vary somewhat from the values shown due to the variability of filtration parameters.

Testing was conducted using the single-pass test method, water at 2.5 gpm/10" cartridge. Contaminants included latex beads, coarse and fine test dust. Removal efficiencies were determined using dual laser source particle counters.

REMOVAL EFFICIENCY

Beta Ratio Efficiency	Beta 50 98%	Beta 10 90%
0.2 µm	0.28	0.20
0.25 µm	0.35	0.25
0.45 µm	0.6	0.45
0.5 µm	0.7	0.5
1 µm	1.5	1.0
2 µm	2.7	2.0
5 µm	7.0	5.0
10 µm	12.0	10.0
25 µm	32.0	25.0
50 µm	70.0	50.0

$$\text{Beta Ratio} = \frac{\text{Upstream particle counts}}{\text{Downstream particle counts}}$$

FOR MORE INFORMATION

GTX-262 9-24

Customer Service/Technical Support: 1-888-353-0303

China: +86-21-5238-6576 Asia: +65-9671-9966

DISTRIBUTED BY

All information and recommendations appearing in this bulletin concerning the use of products described herein are based on tests believe to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Graver Technologies as to the effects of such use or the results to be obtained. Graver Technologies assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations. PMC is a trademark of Graver Technologies, LLC.



Graver Technologies | 200 Lake Drive, Glasgow, DE 19702 | 1-302-731-1700 | 800-249-1990
Fax: 1-302-369-0938 | info@gravertech.com | www.gravertech.com

A member of The Marmon Group—A Berkshire Hathaway Company