



MODEL NUMBER	MEDIA
HT118-00-CR	FULLERS EARTH
AT118-00-CR	ACTIVATED ALUMINA

THE INFORMATION AND DATA CONTAINED HEREIN CONFORMS TO ASME Y14.5-M 1994

DRAWING STATUS

B	CARTRIDGE RE-DESIGNED	ROC	02/25/97	LTH
A	REVISED DECIMAL DIMENSIONS	LTH	12/5/94	LTH
LTR	DESCRIPTION	BY	DATE	APP

REVISIONS

PRODUCTION

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE WITHOUT WRITTEN PERMISSION FROM THE HILLIARD CORP.
 © COPYRIGHT THE HILLIARD CORPORATION, ALL RIGHTS RESERVED.

UNLESS OTHERWISE SPECIFIED:
 BREAK CORNERS CHAMFERED
 UNLESS OTHERWISE SPECIFIED: 45° MAX

UNLESS OTHERWISE SPECIFIED:
 FINISHES: -A 1/16
 -B 1/32
 -C 1/64
 -D 1/128
 -E 1/256
 -F 1/512

MADE FROM

THE HILLIARD CORPORATION
 100 WEST FOURTH STREET
 ELMSHAW, NEW YORK 14002

DRAWN BY GF 01/17/97
 CHECKED BY GLF 01/17/97
 APPROVED BY JMB 01/22/97

SIMILAR TO:
 SCALE: 3/4

TITLE
 DATA SHEET
 HT118-00-CR
 AT118-00-CR

SHEET 1 OF 1

DD-700-49

C